

## Horiba Cardy Twin EC Meter

*Ideal for greenhouse applications*

A pocket-sized conductivity meter packed with advanced features. This ultra-slim meter features push-button auto-calibration, and automatic temperature compensation. The Cardy Twin EC's miniature sensor accurately measures even a single drop of saturated media extract. Ideal for greenhouse and field applications.

Range: 0–199  $\mu\text{S}/\text{cm}$ , 0–19.0  $\text{mS}/\text{cm}$ ;  
Resolution: 1  $\mu\text{S}/\text{cm}$ , 0.01  $\text{mS}/\text{cm}$ ;  
Accuracy:  $\pm 2\%$ ; Auto Temp. Compensation.

Includes: batteries, case, standard solution and instructions.

Item 2205	Cardy Twin EC Meter
Item 2210	Cardy Twin EC Refill Solution
Item 2242	Replacement Sensor



## Waterproof EC Meter

One high accuracy multi-range sensor measures four parameters (Conductivity, TDS, Salinity and Temperature).

### Key Features:

- Auto-ranging meter offers 3 ranges to measure from pure water to saline solution or waste, boiler and cooling water using the same conductivity cell.
- 6 units of measure:  $\mu\text{S}/\text{cm}$ ,  $\text{mS}/\text{cm}$ , ppm, ppt, mg/L, and g/L
- Internal memory stores up to 15 labeled readings for easy recall
- Adjustable conductivity to TDS ratio factor from 0.4 to 1.0
- Self calibration on power-up

Includes: conductivity cell, protective sensor cap, sample cup with cap, four SR44W button batteries, and 48in/1.2m neckstrap. Standards sold separately.

Item 2246	Waterproof EC Meter
Item 2251	Conductivity Standard, 1.41 $\text{mS}/\text{cm}$ , 230ml

